UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/552,996	10/10/2006	Hiroshi Matsuda	00684.102864.	5856
	7590 12/24/200 CCELLA HARPER &	EXAMINER		
30 ROCKEFELLER PLAZA			SAHLE, MAHIDERE S	
NEW YORK, NY 10112			ART UNIT	PAPER NUMBER
			2873	
			MAIL DATE	DELIVERY MODE
			12/24/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)		
	10/552,996	MATSUDA ET AL.		
Office Action Summary	Examiner	Art Unit		
	MAHIDERE S. SAHLE	2873		
The MAILING DATE of this communication ap Period for Reply	pears on the cover sheet with the o	correspondence address		
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING ID. - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutoring. - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION 136(a). In no event, however, may a reply be timed to the second	N. mely filed the mailing date of this communication. ED (35 U.S.C. § 133).		
Status				
1) ☐ Responsive to communication(s) filed on 13 A 2a) ☐ This action is FINAL . 2b) ☐ Thi 3) ☐ Since this application is in condition for allowated closed in accordance with the practice under	is action is non-final. ance except for formal matters, pro			
Disposition of Claims				
4) ☐ Claim(s) 1-9,13,15 and 17-21 is/are pending in 4a) Of the above claim(s) is/are withdrases 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-9,13,15 and 17-21 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/one.	awn from consideration.			
Application Papers				
9) The specification is objected to by the Examin 10) The drawing(s) filed on is/are: a) ac Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the E	cepted or b) objected to by the drawing(s) be held in abeyance. Section is required if the drawing(s) is ob	e 37 CFR 1.85(a). ojected to. See 37 CFR 1.121(d).		
Priority under 35 U.S.C. § 119				
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 				
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail D 5) Notice of Informal F 6) Other:	ate		

DETAILED ACTION

Claims 1-9, 13, 15 and 17-21 are pending in this application.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1-4, 6-9, 13, 15, 17-18 and 20-21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ikeda et al. (USPG Pub No. 2003/0048521) in view of Akins et al. (USP No. 6,166,787).

Regarding claim 1, Ikeda et al. discloses a display apparatus (paragraph 0032, line 1), comprising: a substrate on which a plurality of closed spaces are two-dimensionally disposed along a surface of said substrate (paragraph 0032, lines 3-6), a plurality of particles (5) contained in each of the closed spaces (paragraph 0032, lines 6-9), and a reflection surface for reflecting light which enters each of the closed spaces (paragraph 0068, lines 5-6), wherein said particles (5) are moved in each closed space (paragraph 0042), between a first position at which they are diffused to cover said reflection surface and a second position at which they are collected to expose said reflection surface (see figures 4A-B), to change an intensity of reflected light so as to provide a bright display state and a dark display state (paragraph 0043), with at least a

Application/Control Number: 10/552,996

Art Unit: 2873

part of the reflection surface diffuse-reflecting incident light with a directivity when said particles are located at the second position at which the reflection surface is exposed (paragraph 0068, lines 8-11). Ikeda et al. discloses the claimed invention except for wherein a light intensity of the diffuse reflection with the directivity has such an angular distribution that: (1) an amount of reflected light toward the second position at which said particles are collected is smaller than that thereof in the case where the reflection surface is an isotropic diffuse reflection surface, and (2) an amount of reflected light toward positions other than the position at which said particles are collected is larger than that of reflected light toward the position at which said particles are collected. In the same field of endeavor, Akins et al. discloses wherein a light intensity of the diffuse reflection with the directivity has such an angular distribution that: (1) an amount of reflected light toward the position at which said particles are collected is smaller than that thereof in the case where the reflection surface is an isotropic diffuse reflection surface (col. 7, lines 26-31), and (2) an amount of reflected light toward positions other than the position at which said particles are collected is larger than that of reflected light toward the position at which said particles are collected (col. 7, lines 26-31). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with the light intensity of the diffuse reflection with the directivity has such an angular distribution that: (1) an amount of reflected light toward the position at which said particles are collected is smaller than that thereof in the case where the reflection surface is an isotropic diffuse reflection surface, and (2) an amount of reflected light toward positions other than the position at

Page 3

which said particles are collected is larger than that of reflected light toward the position at which said particles are collected of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Regarding claim 2, Ikeda et al. discloses a display apparatus (paragraph 0032, line 1), comprising: a substrate on which a plurality of closed spaces are twodimensionally disposed along a surface of said substrate (paragraph 0032, lines 3-6), a plurality of particles (5) contained in each of the closed spaces (paragraph 0032, lines 6-9), a partition wall (3) for dividing the closed spaces into each of the closed spaces in a direction along the surface of the substrate (see figure 1, paragraph 0044, lines 1-2), and a reflection surface for reflecting light which enters each of the closed spaces (paragraph 0068, lines 5-6), wherein said particles (5) are moved in each closed space (paragraph 0042), between a first position at which they are diffused to cover said reflection surface and a second position at which they are collected to expose said reflection surface (see figures 4A-B), to change an intensity of reflected light so as to provide a bright display state and a dark display state (paragraph 0043), with at least a part of the reflection surface diffuse-reflecting incident light with a directivity when said particles are located at the second position at which the reflection surface is exposed (paragraph 0068, lines 8-11). Ikeda et al. discloses the claimed invention except for a light intensity of the diffuse reflection with the directivity has such an angular distribution that: (1) an amount of reflected light toward the partition wall is smaller than that thereof in the case where the reflection surface is an isotropic diffuse reflection surface (col. 7, lines 26-31), and (2) an amount of reflected light toward portions other than the partition

wall is larger than that of reflected light toward the partition wall (col. 7, lines 26-31). In the same field of endeavor, Akins et al. discloses a light intensity of the diffuse reflection with the directivity has such an angular distribution that: (1) an amount of reflected light toward the partition wall is smaller than that thereof in the case where the reflection surface is an isotropic diffuse reflection surface, and (2) an amount of reflected light toward portions other than the partition wall is larger than that of reflected light toward the partition wall. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with a light intensity of the diffuse reflection with the directivity has such an angular distribution that: (1) an amount of reflected light toward the partition wall is smaller than that thereof in the case where the reflection surface is an isotropic diffuse reflection surface, and (2) an amount of reflected light toward portions other than the partition wall is larger than that of reflected light toward the partition wall of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Regarding claim 3, Ikeda et al. discloses wherein the reflection surface has a portion close to the second position at which the particles (5) are collected (paragraph 0043, lines 4-9). Ikeda et al. discloses the claimed invention except for the directivity at the portion is stronger than those at other portions of the reflection surface. In the same field of endeavor, Akins et al. discloses the directivity at the portion is stronger than those at other portions of the reflection surface (col. 7, lines 18-31). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with the directivity at the portion is

Application/Control Number: 10/552,996

Art Unit: 2873

stronger than those at other portions of the reflection surface of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Page 6

Regarding claim 4, Ikeda et al. discloses the claimed invention except for wherein the angular distribution of the intensity of light from the reflection surface is such that it is asymmetrical with respect to a direction of a normal to the reflection surface in an area close to the second position at which the particles are collected so as to be localized toward a direction apart from the second position and that it is substantially symmetrical with respect to the normal direction in an area other than the area close to the second position. In the same field of endeavor, Akins et al. discloses wherein the angular distribution of the intensity of light from the reflection surface is such that it is asymmetrical with respect to a direction of a normal to the reflection surface in an area close to the second position at which the particles are collected so as to be localized toward a direction apart from the second position and that it is substantially symmetrical with respect to the normal direction in an area other than the area close to the second position or the partition wall (see figure 1, col. 7, lines 26-31). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with the angular distribution of the intensity of light from the reflection surface is such that it is asymmetrical with respect to a direction of a normal to the reflection surface in an area close to the second position at which the particles are collected so as to be localized toward a direction apart from the second position and that it is substantially symmetrical with respect to the normal direction in an area other than the area close to the second

position or the partition wall of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Regarding claim 6, Ikeda et al. discloses wherein the reflection surface is substantially a mirror surface in an area close to the second position at which the particles are collected (paragraph 0074, lines 11-13), and is a diffuse reflection surface in an area other than the area close to the second position (paragraph 0068, lines 5-11).

Regarding claim 7, Ikeda et al. discloses wherein at least a second portion of the reflection surface in an area close to the position at which the particles are collected is inclined upward (see figures 2C-D, 4B).

Regarding claim 8, Ikeda et al. discloses wherein at least a portion of the substrate is transparent (paragraph 0040, lines 1-2). Ikeda et al. discloses the claimed invention except for the reflection surface is semitransparent, and a light source is disposed below the substrate. In the same field of endeavor, Akins et al. discloses the reflection surface is semitransparent (col. 7, lines 20-22), and a light source is disposed below the substrate (col. 7, lines 22-28). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with the reflection surface is semitransparent, and a light source is disposed below the substrate of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Regarding claim 9, Ikeda et al. discloses wherein the apparatus further comprises a front scattering layer disposed on an observer's side (paragraph 0068, lines 5-11).

Regarding claim 13, Ikeda et al. discloses wherein in each of the closed spaces (paragraph 0044, lines 1-2). Ikeda et al. discloses the claimed invention except for a color filter is disposed on the reflection surface. In the same field of endeavor, Akins et al. discloses a color filter (20) is disposed on the reflection surface (16) (col. 7, lines 18-20). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with a color filter is disposed on the reflection surface of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Regarding claim 15, Ikeda et al. discloses wherein in each of the closed spaces (paragraph 0044, lines 1-2), and the transparent electrode (see figure 3, paragraph 0040, lines 1-2). Ikeda et al. discloses the claimed invention except for a color filter is disposed between the reflection surface and the transparent electrode. In the same field of endeavor, Akins et al. discloses a color filter (20) is disposed between the reflection surface (16) (col. 7, lines 18-20). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with a color filter is disposed between the reflection surface of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Regarding claim 17, Ikeda et al. discloses wherein the reflection surface (6) has a portion close to the partition wall (3), and the directivity at the portion is stronger than those at other portions of the reflection surface (see figure 4A).

Regarding claim 18, Ikeda et al. discloses the claimed invention except for wherein the angular distribution of the intensity of light from the reflection surface is such that it is asymmetrical with respect to a direction of a normal to the reflection surface in an area close to the partition wall so as to be localized toward a direction apart from the second position and that it is substantially symmetrical with respect to the normal direction in an area other than the area close to the partition wall. In the same field of endeavor, Akins et al. discloses wherein the angular distribution of the intensity of light from the reflection surface is such that it is asymmetrical with respect to a direction of a normal to the reflection surface in an area close to the partition wall so as to be localized toward a direction apart from the second position and that it is substantially symmetrical with respect to the normal direction in an area other than the area close to the partition wall (see figure 1, col. 7, lines 26-31). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. with wherein the angular distribution of the intensity of light from the reflection surface is such that it is asymmetrical with respect to a direction of a normal to the reflection surface in an area close to the partition wall so as to be localized toward a direction apart from the second position and that it is substantially symmetrical with respect to the normal direction in an area other than the area close to the partition wall of Akins et al. for the purpose of enhancing a viewer's perceived brightness of the display (col. 1, lines 9-10).

Regarding claim 20, Ikeda et al. discloses wherein the reflection surface is substantially a mirror surface in an area close to the partition wall, and is a diffuse

reflection surface in an area other than the area close to the partition wall (see figures 3-4B, paragraph 0068).

Regarding claim 21, Ikeda et al. discloses wherein at least a portion of the reflection surface in an area close to the partition wall is inclined upward (see figures 3-4B).

Claims **5 and 19** are rejected under 35 U.S.C. 103(a) as being unpatentable over Ikeda et al. (USPG Pub No. 2003/0048521) in view of Akins et al. (USP No. 6,166,787), as applied to claim 4 above, and further in view of Iwai et al. (JPO 11-109392).

Regarding claim 5, Ikeda et al. in view of Akins et al. discloses particles (5) (see figure 1 of Ikeda et al. reference). Ikeda et al. in view of Akins et al. discloses the claimed invention except for wherein the reflection surface is divided into a plurality of reflection areas different in reflection characteristic from each other, and the angular distribution of the intensity of light from each of the divided reflection areas is such that it is changed stepwise or continuously from a strong level to a weak level with respect to the directivity with an increasing distance of the particles from the second position at which the particles are collected and that it is changed stepwise or continuously from a large level to a small level or no level with respect to the asymmetry with the increasing distance. In the same field of endeavor, Iwai et al. discloses the reflection surface (8a) is divided into a plurality of reflection areas different in reflection characteristic from each other (see figure 12), and the angular distribution of the intensity of light from each of the divided reflection areas is such that it is changed stepwise or continuously from a

Page 11

Art Unit: 2873

strong level to a weak level with respect to the directivity and that it is changed stepwise or continuously from a large level to a small level or no level with respect to the asymmetry with the increasing distance (see figure 12, paragraphs 0082-0083). Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. in view of Akins et al. with the reflection surface is divided into a plurality of reflection areas different in reflection characteristic from each other, and the angular distribution of the intensity of light from each of the divided reflection areas is such that it is changed stepwise or continuously from a strong level to a weak level with respect to the directivity and that it is changed stepwise or continuously from a large level to a small level or no level with respect to the asymmetry with the increasing distance of Iwai et al. for the purpose of obtaining a wide angle of visual field and improving reflectance, contrast and color purity (abstract of Yoshio et al. reference).

Regarding claim 19, Ikeda et al. in view of Akins et al. discloses particles (5) (see figure 1 of Ikeda et al. reference). Ikeda et al. in view of Akins et al. discloses the claimed invention except for wherein the reflection surface is divided into a plurality of reflection areas different in reflection characteristic from each other, and the angular distribution of the intensity of light from each of the divided reflection areas is such that it is changed stepwise or continuously from a strong level to a weak level with respect to the directivity with an increasing distance of the particles from the partition wall, and that it is changed stepwise or continuously from a large level to a small level or no level with respect to the asymmetry with the increasing distance. In the same field of endeavor,

Iwai et al. discloses the reflection surface (8a) is divided into a plurality of reflection areas different in reflection characteristic from each other (see figure 12), and the angular distribution of the intensity of light from each of the divided reflection areas is such that it is changed stepwise or continuously from a strong level to a weak level with respect to the directivity and that it is changed stepwise or continuously from a large level to a small level or no level with respect to the asymmetry with the increasing distance (see figure 12, paragraphs 0082-0083). Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the display apparatus of Ikeda et al. in view of Akins et al. with the reflection surface is divided into a plurality of reflection areas different in reflection characteristic from each other, and the angular distribution of the intensity of light from each of the divided reflection areas is such that it is changed stepwise or continuously from a strong level to a weak level with respect to the directivity and that it is changed stepwise or continuously from a large level to a small level or no level with respect to the asymmetry with the increasing distance of Iwai et al. for the purpose of obtaining a wide angle of visual field and improving reflectance, contrast and color purity (abstract of Yoshio et al. reference).

Response to Arguments

Applicant's arguments filed 08/13/2008 have been fully considered but they are not persuasive.

In response to applicant's argument that the examiner's conclusion of obviousness is based upon improper hindsight reasoning, it must be recognized that

Application/Control Number: 10/552,996 Page 13

Art Unit: 2873

any judgment on obviousness is in a sense necessarily a reconstruction based upon hindsight reasoning. But so long as it takes into account only knowledge which was within the level of ordinary skill at the time the claimed invention was made, and does not include knowledge gleaned only from the applicant's disclosure, such a reconstruction is proper. See *In re McLaughlin*, 443 F.2d 1392, 170 USPQ 209 (CCPA 1971).

Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to MAHIDERE S. SAHLE whose telephone number is

Application/Control Number: 10/552,996 Page 14

Art Unit: 2873

(571)270-3329. The examiner can normally be reached on Monday thru Thursday 7:30

AM to 5:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Ricky Mack can be reached on 571 272-2333. The fax phone number for

the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

MSS

12/18/2008

/Ricky L. Mack/

Supervisory Patent Examiner, Art Unit 2873